



BONDIT TILE MATE

Nexgen Construction Supplements



WWW.BONDIT.IN

BONDIT TILE MATE

POLYMER BASED TILE JOINT FILLER

DESCRIPTION

BONDIT TILE MATE is polymer based cementitious tile joint filler used in filling gaps and levels to give long-lasting, dust free tile joints.

BONDIT TILE MATE avoids allow water or moisture to seep into the back of the tile and cause its dislocation. BONDIT TILE MATE firmly holds tiles together and hence gives tiles a long life to the floor tiles. BONDIT TILE MATE can be used for filling joints up to 6 mm width.

ADVANTAGES / BENEFITS

BONDIT TILE MATE prevents water seepage. BONDIT TILE MATE is easy to use and clean. BONDIT TILE MATE makes joint long-lasting, as it's compressive, flexural and tensile strengths are very high.

BONDIT TILE MATE is polymer based and also is non-dusting.

DIRECTIONS FOR USAGE

Mix 3 parts of BONDIT TILE MATE to one part of water by volume to a stiff consistency and leave for 10 minutes. Remix and apply the paste to the tile joints with sponge or towel. Surplus BONDIT TILE MATE should be removed with a wet sponge.

The joint filler becomes dry in a day. Polish the tile with a clean and dry cloth.

SHELF LIFE

| | |
|-------------------|----------------------------|
| Over coating time | (after 20-24 hours @ 30oC) |
|-------------------|----------------------------|

DIRECTIONS FOR USAGE

BONDIT PROOF IWP2 is to be mixed with cement at a rate of 0.75 kg per 50 kg of cement Mix them uniformly with the other dry ingredients of concrete. Add the normal quantity of water. Use the concrete mix only after ensuring that the BONDIT PROOF IWP2 has been uniformly mixed in it. Attention must be paid to the ASTM, BS, DIN and IS specifications relating to mixing times and general conditions for production, application and curing of concrete.

Typical results of permeability as per IS 2645-1975

| | |
|------------------------|------|
| Control | 100% |
| With BONDIT PROOF IWP2 | 17% |

SHELF LIFE

12 months

SUPPLY

BONDIT TILE MATE comes in 1 Kg packs

COVERAGE

Coverage depends on the size of the tile and the width of the joint, for 3mm deep joints coverage is given in the following table:

TILE SIZES

| joint width | 6"X6" | 6"X12" | 4"X8" | 8"X8" | 8"X12" | 10"X10" | 12"X12" |
|-------------|-------|--------|-------|-------|--------|---------|---------|
| 2mm | 95 | 128 | 88 | 128 | 152 | 158 | 186 |
| 3mm | 62 | 86 | 60 | 84 | 100 | 106 | 125 |
| 4mm | 48 | 65 | 44 | 63 | 75 | 81 | 92 |
| 6mm | 31 | 44 | 30 | 44 | 52 | 52 | 63 |

IMPORTANT NOTE

BONDIT products undergo high standard quality checks and every reasonable precaution is taken in the manufacture of all products. BONDIT continuously strive to ensure the products, recommendations, specifications & information given is reliable, correct and accurate. No specific guarantee can be assured as product performance depends not only on quality but also on many other factors which are not under our control. The customer should make his own trials to determine the compatibility of the product for his own purpose. All products are sold subject to our standard terms and conditions of sale.

BONDIT CONSTRUCTION CHEMICAL PVT LTD.

Office No. 3&4, Sai Prithvi Arcade, 1st Floor, Above Bata Showroom
Main Road, Madhapur, Hyderabad, Telangana



Customer : 07997 109 109



service@bondit.in