



BONDIT TILE ADHESIVE

Nexgen Construction Supplements



WWW.BONDIT.IN

BONDIT TILE ADHESIVE

Tile Fixing Adhesive

DESCRIPTION

BONDIT TILE ADHESIVE is a unique formulation which has excellent adhesive property in fixing tiles. This is also suitable for the bonding of different construction materials in interior and exterior areas

ADVANTAGES / BENIFITS

- BONDIT TILE ADHESIVE gives an impermeable layer.
- It can be easily applied and hence highly workable.
- It has special additives which minimise shrinkage in the system..
- It can be used to bond gypsum boards and styro foam to other substrates.

CHARACTERISTICS

Colour	Grey
Base	Cement with modified special polymers
Working Temperature	30°C
Pot Life	30 Minutes
Movement	Nil
Absorption	

SPECIFICATIONS

BONDIT TILE ADHESIVE complies with DIN 18156 Part 2(thin bed mortar), Application specification DIN 18156 Part 1.

AREAS OF APPLICATIONS

BONDIT TILE ADHESIVE can be used to lay ceramic tiles, quartz tiles, terrazzo tiles on all types of surfaces. It can be used for bonding tiles in balconies, terraces,floors,bathrooms etc.,

DIRECTIONS FOR USE

The surface where BONDIT TILE ADHESIVE is to be applied should be free from dust, grease and oil. All holes in the substrate have to be filled up and levelled. The surface should be slightly moist for better results. During application surface must be free from rising dampness and other hydrostatic pressure.

It has to be added to water while stirring, 3 parts by volume of BONDIT TILE ADHESIVE has to be mixed with 1 part by volume of water. After first mixing, remix the BONDIT TILE ADHESIVE after 5 minutes. Ensure uniform lump free mixing.

Approximately 2.5 to 3 Kg/m² of BONDIT TILE ADHESIVE has to be applied depending upon the surface and type of tile. Apply only as much BONDIT TILE ADHESIVE as can be fixed with tiles within next 25 mts. For better results use notch trowels.

PRECAUTIONS

BONDIT SUPER PLAST S1 is non-toxic, non-flammable. Splashes if any should be washed with plenty of water. When it comes in contact with eyes, take doctor's advice.

SHELF LIFE

6 Months

SUPPLY

BONDIT TILE ADHESIVE comes in 25 Kg packs.

TECHNICAL SUPPORT


Technical information and guidance regarding BONDIT range of admixtures, repairs and bonding, water proofing systems, epoxy industrial flooring systems etc., will be available from the technical services department, BONDIT CONSTRUCTION CHEMICALS PVT LTD.

IMPORTANT NOTE

BONDIT products undergo high standard quality checks and every reasonable precaution is taken in the manufacture of all products. BONDIT continuously strive to ensure the products, recommendations, specifications & information given is reliable, correct and accurate. No specific guarantee can be assured as product performance depends not only on quality but also on many other factors which are not under our control. The customer should make his own trials to determine the compatibility of the product for his own purpose. All products are sold subject to our standard terms and conditions of sale.

BONDIT CONSTRUCTION CHEMICAL PVT LTD.

Office No. 3&4, Sai Prithvi Arcade, 1st Floor, Above Bata Showroom
Main Road, Madhapur, Hyderabad, Telangana

 Customer : 07997 109 109

 service@bondit.in